


## Штуцер под приварку

### DAS

DAS.FLD.RU



Серия	Заказной код	Наружный диаметр	D	H	h	L	l	PN(бар)	
								Угл.сталь	SS316
L	DAS-06L.FLD.RU	6	10	14	12	29	14.0	315	315
	DAS-08L.FLD.RU	8	12	17	14	31	16.0	315	315
	DAS-10L.FLD.RU	10	14	19	17	33	18.0	315	315
	DAS-12L.FLD.RU	12	16	22	19	33	18.0	315	315
	DAS-15L.FLD.RU	15	19	27	22	37	22.0	315	315
	DAS-18L.FLD.RU	18	22	32	27	40	23.5	315	315
	DAS-22L.FLD.RU	22	27	36	32	45	28.5	160	160
	DAS-28L.FLD.RU	28	32	41	41	47	30.5	160	160
	DAS-35L.FLD.RU	35	40	50	46	54	32.5	160	160
DAS-42L.FLD.RU	42	46	60	55	58	35.0	160	160	
S	DAS-06S.FLD.RU	6	11	17	14	34	19.0	630	630
	DAS-08S.FLD.RU	8	13	19	17	36	21.0	630	630
	DAS-10S.FLD.RU	10	15	22	19	39	22.5	630	630
	DAS-12S.FLD.RU	12	17	24	22	41	24.5	630	630
	DAS-14S.FLD.RU	14	19	27	24	45	27.0	630	630
	DAS-16S.FLD.RU	16	21	30	27	45	26.5	400	400
	DAS-20S.FLD.RU	20	26	36	32	51	29.5	400	400
	DAS-25S.FLD.RU	25	31	46	41	56	32.0	400	400
	DAS-30S.FLD.RU	30	36	50	46	62	35.5	400	400
	DAS-38S.FLD.RU	38	44	60	55	69	38.0	315	315

По умолчанию уплотнительное кольцо O-Ring поставляется из материала NBR, либо Viton по запросу (стр. 126)